



ATARRI  
6-7 March 2025, Limassol, Cyprus

# GRASP and satellite-based data for Lidar ratio retrievals

**Anna Moustaka**


*PhD Candidate*

*Department of Applied and Environmental Physics  
School of Physics  
Aristotle University of Thessaloniki (AUTH)*




[anna.moustaka@pmodwrc.ch](mailto:anna.moustaka@pmodwrc.ch)

## Combining retrievals from the active and passive sensors of the A-Train constellation (namely CALIOP, POLDER-3, MODIS)




<https://atrain.nasa.gov/>



Moustaka et al. (2025) – Under review

Definition of dust lidar ratio across North Africa and the Middle East



Kok et al. (2023)

## Sea salt



## Smoke



## Volcanic ash



## Dust



Floutsi et al. (2023)



## Pollution



# Why does Lidar ratio vary?

- Shape
- Size
- Chemical composition

Reid et al. (2003)




**Complex refractive index**

$$m = n_r - i \cdot n_i$$


$$n_r = 1.4$$

$$n_r = 1.5$$

$$n_r = 1.6$$



- **Aerosol Optical Depth [AOD]**
- Aerosol typing
- Aerosols' microphysical properties




$$S_{aer} = \frac{\sigma_{aer}}{\beta_{aer}}$$


????

$$\sigma_{aer} = S_{aer} \cdot \beta_{aer}$$

**Dust, smoke,...??**




- Aerosol Optical Depth [AOD]
- **Aerosol typing**
- Aerosols' microphysical properties




e.g. ATLID on  
EARTHCARE  
mission

- Aerosol Optical Depth [AOD]
- Aerosol typing
- **Aerosols' microphysical properties**



- Shape
- Size
- Chemical composition




- Studies.. LR redefinition towards a better representation of AOD and DREs
- Easy to identify due to its non-spherical shape




Amiridis et al. (2013)



Reid et al. (2003)




# Datasets




<https://atrain.nasa.gov/>

## Light Detection And Ranging ... LIDAR



Elastic backscatter lidar



Backscatter signal

Winker et al. (2010)

$\delta_\lambda = 0$  Spherical


$\delta_\lambda > 0$  Non-Spherical

Optical analyzer/  
Detectors


Dust identification

Accurate depolarization measurements

$$\delta_\lambda = \frac{\beta_\lambda^\perp}{\beta_\lambda^\parallel}$$



Baumgardner et al. (2014)




## POLarization and Directionality of the Earth's Reflectances ... passive instrument ... reflectance at the top of the atmosphere (TOA)

### POLDER-3/GRASP-Components

AOD along with other aerosol and surface properties..

General structure of inversion algorithm



Li et al. (2019)

Parameters	Dimension	Description
AOD	( $\lambda$ , latitude, longitude)	Aerosol optical depth
AExp	(latitude, longitude)	AE (670/865 nm)
AODF	( $\lambda$ , latitude, longitude)	Fine-mode AOD
AODC	( $\lambda$ , latitude, longitude)	Coarse-mode AOD
AAOD	( $\lambda$ , latitude, longitude)	Aerosol absorption optical depth
SSA	( $\lambda$ , latitude, longitude)	Single-scattering albedo
RealRefIndSpect	( $\lambda$ , latitude, longitude)	Real part of refractive index
ImagRefIndSpect	( $\lambda$ , latitude, longitude)	Imaginary part of refractive index
SizeDistrLogNormBin	(five, latitude, longitude)	Five bins of size distribution
SphereFraction	(latitude, longitude)	Sphere fraction
VertProfileHeight	(latitude, longitude)	Aerosol scale height (unit: m)
LandPercentage	(latitude, Longitude)	Land percentage (%)
ResidualRelative	(latitude, longitude)	Relative residual

$\lambda = 443, 490, 565, 670, 865$  and  $1020$  nm.


Dubovik et al. (2011, 2014, 2021); Li et al. (2019)

MODerate resolution Imaging Spectroradiometer  
 ... passive instrument ... reflectance at the top of the atmosphere (TOA)




## MODIS-Aqua AOD

## MERRA-2 Dust Fraction (MDF)




## MIDAS DOD



Gkikas et al. (2021)


# Methodology





Ginoux et al. (2012); Winker et al. (2013)

## CALIOP-CALIPSO Dust identification



## POLDER-3/GRASP- Components

Time period: 2006-2009 [1°x1°]

- AOD
  - SSA
  - Refractive Indices,
  - ...
- Dubovik et al. (2011, 2014, 2021); Li et al. (2019)


## MIDAS

Time period: 2007-2017 [1°x1°]

- DOD

Gkikas et al., (2021)

## Dust identification



**DOD<sub>CALIPSO</sub>**

**DOD<sub>POLDER-3/GRASP</sub>**

**DOD<sub>MIDAS</sub>**

Adjustment of dust LR until..


$$\text{DOD}_{\text{CALIOP}} = \text{DOD}_{\text{POLDER-3/GRASP}}$$

$$\text{DOD}_{\text{CALIOP}} = \text{DOD}_{\text{MIDAS}}$$

LR<sub>updated</sub> instead of 44 sr


# Results

# Comparison of DOD retrievals



North Africa Underestimation of DOD

Middle East Overestimation of DOD



Over/UnderEstimation of DOD can be reduced after adjusting dust lidar ratio

Moustaka et al. (2024); Konsta et al. (2018); Amiridis et al. (2013); Omar et al. (2013), and others..


# Dust LR

Adjustment of dust LR until..


$$\text{DOD}_{\text{CALIOP}} = \text{DOD}_{\text{POLDER-3/GRASP}}$$
$$\text{DOD}_{\text{CALIOP}} = \text{DOD}_{\text{MIDAS}}$$

LR<sub>updated</sub> instead of 44 sr


# Dust LR distribution [2006-2009] CALIOP-POLDER-3/GRASP Components



# Dust LR distribution [2007-2017] CALIOP-MIDAS







# Evaluation against AERONET



[https://aeronet.gsfc.nasa.gov/new\\_web/aerosols.html](https://aeronet.gsfc.nasa.gov/new_web/aerosols.html)

- Identification of CALIPSO orbits nearby AERONET sites
  - ❑ CALIPSO orbits residing within a circle of 100 km radius centered at an AERONET station
  - ❑ AERONET observations within a  $\pm 30$  min time window centered at the CALIPSO overpass time
- Clear sky conditions based on the CALIPSO classification scheme
- Laser beam penetrates throughout the atmosphere reaching at the ground level
- Dust should be at least the 95% of the total aerosol records
- The elevation difference between the AERONET site and CALIPSO mean ground track elevation should be below 100 m (Amiridis et al. 2015)
- The elevation slope in the CALIPSO overpass are constrained to be less than 400 m (Amiridis et al. 2015)






????

$$\sigma_{aer} = S_{aer} \cdot \beta_{aer}$$


Station #	DOD CALIPSO	DOD AERONET
	0.23	0.26

## 4. 44 sr - CALIPSO def


1.




2.




3.





(a)



- LR\_diff < 0 means the upgraded LR value is smaller than the default (44 sr)
- LR\_diff > 0 means the upgraded LR value is larger than the default (44 sr)

- ★ LR<sub>POLDER-3/GRASP</sub> - 44 sr
- ★ LR<sub>MIDAS</sub> - 44 sr
- ★ LR<sub>MIDAS SEASONAL</sub> - 44 sr

# DOD climatology



From 2007-2022

1°x1°



- Do LR maps change the DOD?

# DOD ANNUAL [2007-2022]




## CALIPSO default LR




## CALIOP-POLDER-3/GRASP LR



## CALIOP-MIDAS LR









Combining retrievals from active and passive sensors of the A-Train satellite constellation (CALIOP; POLDER-3; MODIS) towards:

- Defining the Annual and Seasonal Dust LR distribution over North Africa and the Middle East
- Performing Climatological analysis across various spatiotemporal scales utilizing the revised Dust LR
- Refined dust LRs improve CALIOP performance in terms of DOD (against AERONET)


Moustaka et al. 2025 – Under review



LR distribution



Evaluation against AERONET



DOD climatology



Thank you for your attention!!!



[anna.moustaka@pmodwrc.ch](mailto:anna.moustaka@pmodwrc.ch)